

DIGITAL LECTERN BMTMMP-01



Space for Internal
Accessories



Gooseneck Mic Provision



External Face Plate



Screen Tilt Control



Multimedia Controller



Motorised Screen
Tilt Mechanism



Gooseneck Mic with
Vol. Control & USB



Digital podium offers lockable console with Multimedia controller, Power management, motorised tilted 22 inch Capacitive touch / EMR touch display, Goosneck mic, wireless mic, wired or witless keyboard, Visualise, Amplifier- Speaker, wireless mic with handheld mic and lapel mic, external out put port, 19 inch Rack for Pc and other Av hardware

SPECIFICATION

CHASSIS

Type of Chassis / Frame	Metallic
Mount Type	Floor Mounted With Wheels
Material of Chassis	Mild Steel
Thickness of Enclosure (mm)	1.5 mm (Min) Stainless Steel Sheet
Screwless Chasis	Yes
Adequate Space For Additional Devices	Yes
Drawers / Cabinets	Yes
If yes, Lockable	Yes

DISPLAY

Screen Size	21.5"
Maximum Resolution	(Full HD) 1920 x 1080@60 HZ
Aspect Ratio	16.9
Response Time	8 ms
Colour Supported	16.7 Million
Brightness	250 cd / M2
Backlight	LED
Viewing Angles	178° Horizontal 178° Vertical
Panel Type	VA (Vertical Alignment)
Stand	Tilt (10°~ 90°)
Speakers	2 x 1 W
Ports & Connector	VGA HDMI R - IN 1xUSB 2.0 up Stream 2xUSB 2.0 Down Stream

BIS REGISTRATION NUMBER UNDER CRS FOR DISPLAY R-41186368

SYSTEM DETAILS

Processor Make	Intel
Processor Series	Intel Core i3,i5,i7
Processor Configuration	Generation 6/7/8/9/10/11/12
Operating System (pre-Loaded)	Windows 10
Antivirus With One Year Liscense	Available
RAM Memory (GB)	4
Storage / HDD (GB)	1024
Built- In Standard Keyboard	Available
Built- In Mouse	Available

BUILT-IN DEVICES

Optical Disk Drive Compatibility	Yes
Inbuilt Speakers	Available
Numbers of Speakers	2
Wattage of Each Speaker (Watt)	50
Central Control Panel	Available
Gooseneck Mic	1
Wireless Mic	1
Handheld Mic	1
Wireless Reciever	1
Amplifier	Available
Amplifier Wattage (Watt)	50

CONSOLE PANEL PORTS

USB 2	2
USB 3	0
VGA Ports	1
HDMI Ports	1
Viedo Pin	1
RJ 45	1
Power Backup Min 30 Minutes	UPS Supplied
Cooling System	Available

GENERIC INFORMATION

Maximum Power Consumption (watt)	120
Operating Temperature Range (Degree C)	May -45
Operating Humidity (RH) (%)	40 Deg at 90% RH non condensing
Storage Humidity (RH) (%)	85
Overall Dimension (cm x cm x cm)	730, 670, 1260
Weight (Kg)	95
BIS Registration Number For Rest of the Components	NA
On Site OEM Warranty In Years	3
Storage Temperature (Degree C)	-10 to 55

VISUALISER

Technology	CMOS
Resolution (pixels)	8 MP
Video Frame Rates (FPS)	30
Optical Zoom	22x
Shooting Area (mm)	A4
Focussing Arrangement	Auto & Manual Both
Layout	Landscape & Portrait Both
Lens Focal Length (mm)	1.3
Digital Magnification	12 x
Image Memory (Number Of Images)	240
Image Rotation Facility (Degree C)	180
Light Source	White Led
Life of Lamp Used (years)	1
USB Port (Number)	1
VGA Port (Number)	2
DVI-1 Port (Number)	0
HDMI Port (Number)	2
RS 232 Port (Number)	1
Network Connectivity	No
Full Function Remote Control	Yes
Light Box	Yes
Accessories	Yes
Operating Temperature Range (Degree C)	0-50
Operating Humidity	0-90
Dimension (mm)	410*370*555
Weight	5.5 Kg